

VIMEK 610.2

VIMEK®

POWERED BY CAT® AND BOSCH REXROTH



Loading capacity at 5000 kg

– more than its own weight.

LED lights as option, increased hydraulic effects

and integrated WiFi module for crane
and valve settings.

Powerful engine at 60 Hp

from CAT and modern hydrostatic
mechanical transmission from
Bosch Rexroth.

Member of our DreamTeam

together with our harvester Vimek
404T6 for modern, low impact and
no branch road thinnings.



TECHNICAL SPECIFICATION

Engine

CAT 2,2T 44 kW / 2700 rpm

Speed

0-18 km/hour

Transmission

Hydrostatic / mechanical

Front tires

500/60-22,5 or 405/70-24

Rear tires

400/60-15,5

Ground clearness

40 cm

Hydraulic

Flow 60 l/min 175 bar

Length

Standard 6,80 m (load length 3,30 m, loading area 1,85 m²)

Short 6,60 m (load length 3,00 m, loading area 1,85 m²)

Long 7,50 m (load length 4,00 m, loading area 1,65 m²)

Width

1,90 m or 2,00 m

Loading capacity

5,000 kg

Weight incl. crane

4,700 Kg

Crane

Mowi P25

– Max reach, 5,20 m

– Lifting capacity at 5,20 m, 400 kg

– Gripping area, 0,16 m²

EXTRA EQUIPMENT

Options

Air condition

Tilttable Grapple 0,16 m²

Crane damping system

Pneumatic chair

Refueling pump for hydraulic oil

Refueling pump for diesel

Radio controlled hydraulic winch

Sun blinds

Diesel engine heating system

Callstart for diesel engine

Roof frame

Full LED lights including roof frame

Half LED lights including roof frame

Sprinkler system

PC with rear camera

Tow hitch

Radio with Bluetooth

Extra accessories

Wheel tracks

Wheel chains 500/60-22,5 or 405/70-24

Bucket attachment

Dolly trailer

Chain saw holder

*Maskinrytjänsterna är utrustade med extra utrustning.

© 2013 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, their respective logos, Caterpillar Yellow, the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and Aug. not be used without permission.

Version 1, Aug 2015

For more information and to find your nearest retailer, please visit our website

www.vimek.se

VIMEK®